



4U rSeries Rack

1SKB-R4U



Available in 2U, 3U, 4U, 6U, 8U, 10U, and 12U sizes, SKB Standard Roto Racks are roto-molded of Polyethylene (LLDPE) for extra strength and durability.

The exteriors feature SKB's recognizable bar design that signifies the rack unit size on the front and rear lids. Molded bars on top and bottom also provide interlocking capabilities allowing you to easily and securely stack them with SKB's Shallow Racks and Roto Rolling Racks, making transport even more convenient and secure. Lids include rubber gasket seals to keep water out. Other standard features include front and rear steel threaded rails and rack screws (10-32 thread), recessed steel Mil-Spec twist latches, flush carry handles, and non-slip rubber feet. All Standard Roto Racks are 17.6" deep from front rail to rear

FEATURES

- Roto molded of Linear Low Density Polyethylene (LLDPE) for maximum strength & impact
- Available in 2U, 3U, 4U, 6U, 8U, 10U, and 12U
- Interlocking molded stacking
- Gasket-sealed waterproof front & rear
- Recessed twist
- Heavy-duty flush mount
- Non-slip rubber
- Includes rack mount
- Optional Roto Caster Board available
- Unconditional Lifetime

SPECIFICATIONS

Exterior	Hard	-
Rack Units	4	-
Front Rail To Back Lid	19.75 in	50.16 cm
Rail To Rail	17.5 in	44.45 cm
Rear Rail to Front Lid	19.75 in	50.16 cm
Product Weight	15.48 lb	7.02 kg
Exterior Length	24 in	60.96 cm
Exterior Width	22.25 in	56.52 cm
Exterior Height	9.5 in	24.13 cm
Carton Length	24.5 in	62.23 cm
Carton Width	23 in	58.42 cm
Carton Height	10 in	25.40 cm
Shipping Weight	17.49 lb	7.93 kg

AVAILABLE CONFIGURATIONS

1SKB-R4U	Black	-
----------	-------	---