



1660 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **4 strong polyurethane wheels with stainless steel bearings**
- **Large 2-person fold down handles**
- **Watertight, crushproof, and dustproof**
- 3 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



1660
Standard



1664
With Padded Dividers



1660NF
No Foam



1660WF
With Foam

DIMENSIONS

Interior (L×W×D)	28.20 x 19.66" x 17.63 (71.6 x 49.9 x 44.8 cm)
Exterior (L×W×D)	31.59 x 22.99" x 19.48 (80.2 x 58.4 x 49.5 cm)
Lid Depth	3.50" (8.9 cm)
Bottom Depth	14.14" (35.9 cm)
Total Depth	17.64" (44.8 cm)
Int Volume	5.66 ft ³ (0.16 m ³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane

Purge Body
Purge Vent

ABS
3 Micron Hydrophobic Non-Woven

COLORS

 Black  Desert Tan  OD Green

WEIGHT

Weight With Foam 42.16 lbs (19.1 kg)
Weight Empty 34.16 lbs (15.5 kg)
Buoyancy 365.00 lbs (165.6 kg)
Master Pack Weight 49.00 lbs (22.2 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C)
Maximum Temperature 210°F (98.9 °C)

CERTIFICATIONS

IP67
Def Stan 81-41

OTHER

Wheels 4
Extendable Handle yes
Master Pack 1
Nameplate yes
Reduced Area yes
Military yes

ACCESSORIES



1661
5 pc. Replacement Foam Set



1662
Pick N Pluck™ Sections Only
(set of 3)



1663
Replacement O-ring



1665
Padded Divider Set




1669
Photo/Lid Organizer



1507
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel



1500CI
Corrosion Intercept Kit

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 09-24-23